









TRINCIA PER ERBA

SHREDDER FOR GRASS



DATI TECNICI

TECHNICAL DATA

CODICE	 cm	 cm	 Hp	 Kg	 r.p.m.	 r.p.m.	 n°	 n°	
TSL 090	090	105	15-20	95	540	2000	2	24	
TSL 100	100	115	15-20	120	540	2000	2	32	
TSL 120	120	135	20-25	130	540	2000	2	32	
TSL 135	135	150	25-30	150	540	2000	2	40	
TSL 160	160	175	25-30	180	540	2000	3	48	
TSL 180	180	195	35-40	210	540	2000	3	56	

DOTAZIONE STANDARD

STANDARD EQUIPMENT

- | | |
|--|--|
| <ul style="list-style-type: none"> • Scatola ingranaggi con ruota libera 540 giri/min • Rullo • Coltelli y universali montati su cavallotto • Attacco fisso • Cofano chiuso • Albero cardanico • Protezioni antinfortunistiche "CE" | <ul style="list-style-type: none"> • Gearbox with fifth wheel 540 r.p.m. • Roller • Universal y - knives fitted on a u-bolt • Fix coupling • Closed casing • Cardan shaft • "CE" accident protections |
|--|--|

ACCESSORI

ACCESSORIES

TSL804	Spostamento idraulico	Hydraulic displacement	
TSL803	Spostamento meccanico	Mechanical displacement	